

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 August 2006 (03.08.2006)

PCT

(10) International Publication Number
WO 2006/080964 A1

(51) International Patent Classification:

G11B 20/12 (2006.01) G11B 7/24 (2006.01)
G11B 7/007 (2006.01)

(21) International Application Number:

PCT/US2005/039321

(22) International Filing Date: 31 October 2005 (31.10.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/646,702 25 January 2005 (25.01.2005) US

(71) Applicant (for all designated States except US): TECH-
NICOLOR INC. [US/US]; 4050 Lankershim Boulevard,
North Hollywood, California 91608 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): TOWN, John,
Matthew [GB/US]; 2963 Cove Trace, Charlottesville,
Virginia 22911 (US).

(74) Agents: TRIPOLI, Joseph, S. et al.; Thomson Licensing
Inc., Two Independence Way Suite 200, Princeton, New
Jersey 08540 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: HIGH DENSITY, HYBRID OPTICAL DISC



(57) Abstract: The present invention advantageously provides a high density, hybrid optical disc and method of manufacture, thereof. In one embodiment of the present invention, a high-density, hybrid optical disc includes first and second disc portions adhesively bonded to each other, each of the disc portions containing at least one transparent substrate and a data layer, where at least one of the first and second disc portions comprises a high density format. The data layer of the second disc portion of the hybrid optical disc is coated with a high transmissive/ low reflective layer and is situated opposite a transparent assembling adhesive layer joining the first and second disc portions.

HIGH DENSITY, HYBRID OPTICAL DISC

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to United States Provisional Patent Application Serial
5 No. 60/646,702, filed January 25, 2005, which is herein incorporated by reference in its entirety.

TECHNICAL FIELD

This invention relates to optical recording discs, and more particularly, to a high
10 density, hybrid optical disc and method of producing the same.

BACKGROUND ART

Optical discs for recording and reproducing information by irradiating the optical discs
with a laser beam exist in various formats such as a read-only type compact disc (CD-DA,
15 CD-ROM), a write-once type compact disc (CD-R), a rewritable type compact disc (CD-RW),
etc. Typically, each of the discs is made of a base board having a diameter of 120 mm and a
thickness of about 1.2 mm and is designed to be recorded and reproduced by a laser beam of
substantially 780 nm.

Further to the compact discs described above, there exist digital versatile discs (DVD).
20 In a DVD, a moving picture can be stored in the disc having the same diameter of 120 mm as
that of the compact disc with an image quality similar to that of a present-day television. The
DVD needs to increase a storage capacity to six to eight times as high as that of the compact
disc. As such, the DVD records and reproduces data by using a laser beam having a
wavelength of typically 635 to 650 nm, which is shorter than the laser beam used for the
25 compact disc or the like. While the compact disc is made of a single board, the DVD is
formed by bonding base boards of 0.6 mm together. A read-only type DVD includes two
types of DVDs. A first one of them is a DVD wherein two base boards having recording
surfaces are bonded together and both the surfaces are used as signal recording surfaces. The
other of them is a DVD wherein a base board having a signal recording surface is bonded to a
30 dummy base board having no signal recording surface and the single surface is used as a
signal recording surface.

Recently another disc called a Blu-ray disc has been introduced having a typical
diameter of 120 mm like the compact disc or the DVD. In the Blu-ray disc, a moving picture

-2-

can be stored with an image quality similar to that of a high definition television. The Blu-ray Disc introduced typically has three types of storage capacity including 23.3 Gbytes, 25 Gbytes and 27 Gbytes. The Blu-ray Disc typically uses a laser beam having a wavelength of approximately 405 nm, far shorter than that of the DVD. Further, the Blu-ray Disc typically
5 has a structure where a recording layer and a reflecting layer are laminated on a disc board having a thickness of 1.1 mm and a transparent cover layer of 0.1 mm on an uppermost layer to ensure a tilt margin.

As described above, a plurality of kinds of optical discs, such as the compact discs, the DVDs, and the Blu-ray Discs are known in the art, however there does not currently exist an
10 optical disc with a combination of these optical disc formats and manufactured in a cost effective manner.

BRIEF SUMMARY OF THE INVENTION

The present invention addresses the deficiencies of the prior art by providing a high
15 density hybrid optical disc and method of manufacture, thereof.

In one embodiment of the present invention, a hybrid optical disc includes first and second disc portions adhesively bonded to each other, each of the disc portions containing at least one transparent substrate and a data layer, where at least one of the first and second disc portions comprises a high density format. The data layer of the second disc portion of the
20 hybrid optical disc is coated with a high transmissive/low reflective layer and is situated opposite a transparent assembling adhesive layer joining the first and second disc portions.

In an alternate embodiment of the present invention, a method for manufacturing a hybrid optical disc of the present invention includes producing a first disc portion by pressing at least a portion of a first transparent substrate to fashion a first data layer according to a first standard, the data layer being coated with a reflecting layer, producing a second disc portion by pressing at least a portion of a second transparent substrate to fashion a second data layer according to a second standard, the second data layer being coated with a high transmissive/low reflective layer and then protected by a protective layer. The method further includes
25 adhesively bonding the two disc portions to each other such that the second data layer of the second disc portion is opposite the adhesive layer, where at least one of the first and second
30 disc portions comprises a high density format.

In yet an alternate embodiment of the present invention, a dual-format, hybrid optical disc includes a first half-disc having a first format and a second half-disc having a second

format, where at least one of the first format and the second format is a high-density format. The first half-disc and the second half-disc are bonded together to make a full-thickness disc such that both formats are read from a common side of the full-thickness disc.

In still an alternate embodiment of the present invention, a method for manufacture of a dual-format, hybrid optical disc of the present invention includes, recording a high-density format on a first side of a first half disc, recording a relatively, lower density format on a first side of a second half disc and bonding the first half disc to the second half disc to provide a dual-format full-thickness hybrid optical disc such that both formats are read from a common side of the full-thickness disc.

BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 depicts a high level block diagram of a high density, hybrid optical BD/DVD disc in accordance with an embodiment of the present invention;

FIG. 2 depicts a flow diagram of a method for manufacturing a BD/DVD disc in accordance with one embodiment of the present invention;

FIG. 3 depicts a high level block diagram of a high density, hybrid optical BD/CD disc in accordance with an alternate embodiment of the present invention; and

FIG. 4 depicts a flow diagram of a method for manufacturing a BD/CD disc, such as the BD/CD of FIG. 3, in accordance with one embodiment of the present invention.

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

DETAILED DESCRIPTION

The present invention advantageously provides a high density hybrid optical disc and method of manufacture, thereof. Although throughout the teachings herein and in various embodiments of the present invention, the aspects of the present invention are described within the context of a high density, hybrid optical disc comprising various specific format combinations, the specific embodiments of the present invention should not be treated as limiting the scope of the invention. It will be appreciated by those skilled in the relevant art and informed by the teachings of the present invention that the concepts of the present invention may be applied for providing high density, hybrid optical discs comprising at least

one high density optical disc portion (half-disc) that may also be combined with substantially any other lower density media portion or portions (half-disc(s)).

In one embodiment of the present invention, a high density, hybrid optical disc in accordance with the present invention comprises a Blu-ray disc (BD) layer and a DVD layer.

5 For example, FIG. 1 depicts a high level block diagram of a high density, hybrid optical BD/DVD disc 100 in accordance with an embodiment of the present invention. As depicted in FIG. 1, the BD/DVD disc 100 of FIG. 1 comprises an outer BD layer 110 and an inner DVD layer 120. The BD/DVD disc 100 is formed in such a way that the DVD layer 120 on which data is recorded on the basis of the DVD standard is bonded to the BD layer 110 on
10 which data is recorded on the basis of the Blu-ray Disc standard using a transparent adhesive layer. The high density, hybrid optical BD/DVD disc 100 comprises a disc that would play in either a DVD player (e.g., 650nm; NA=0.6) and/or a Blu-ray player (e.g., 405nm; NA=0.85.). FIG. 1 further depicts a BD laser 115 and a DVD laser 125 for reading the BD data and the DVD data, respectively.

15 More specifically, in one embodiment the present invention uses DVD half-disc bonding technology (e.g., transparent assembling adhesive layer) to make one dual-format full-thickness disc with both formats read from, in the embodiment of FIG. 1, the same side. The DVD single-layer recording is performed on an A-Side at reverse rotation similar to a Layer-1 Parallel Track Path recording for dual-layer. The DVD single-layer recording is
20 made on the physical surface of the disc analogous to Layer-1 rather than Layer-0 technology. A B-side of the original molded replica is made using a non-standard 0.5mm mold cavity. The B-side stamper is high density (e.g. Blu-ray). The B-side disc is sputtered with a high transmissive/low reflectivity coating suitable for 405nm laser (e.g. silver or silicon hydride). The B-side disc is turned over to have the sputtered data surface on the outside of the disc
25 during bonding. The bonded disc with the B-side data surface on top is spin-coated utilizing, in one embodiment of the present invention, UV-cure lacquers to build up a 0.1mm cover layer. The finished disc receives a label print on the A-side disc surface unlike all other DVD discs. That is, the final high density, hybrid optical BD/DVD disc 100 is printed with a label over the entire surface of the A-side disc. The DVD layer (e.g., 650nm; NA=0.6) is read
30 through the B-side of the disc with the red laser reading through the 0.1mm spin-coated cover-layer and through the high-density data surface to reach the DVD data layer molded on the A-side disc. That is, the BD layer is transparent for the red laser light implemented for the DVD portion. As depicted in FIG. 1, the DVD data layer is approximately 0.6mm from the

outer most surface (e.g., the BD cover layer) of the B-side. Because in the embodiment of FIG. 1 the BD cover layer is 0.1mm, the BD layer and the DVD layer in the embodiment of the invention depicted in FIG. 1 are separated by a transparent layer of approximately 0.5mm.

The finally bonded high density BD/DVD disc 100 is configured such that the
5 reflecting layer of the DVD disc portion is located adjacent to the location of the bond (e.g., adhesive layer) as depicted in FIG. 1.

FIG. 2 depicts a flow diagram of a method for manufacturing a BD/DVD disc, such as the BD/DVD 100 of FIG. 1, in accordance with one embodiment of the present invention. The method 200 of FIG. 2 is entered at step 202 by molding two DVD half discs (elementary
10 discs) using DVD half disc molding technology known in the art, the DVDs comprising a first disc having a thickness of substantially 0.6mm and a second disc having a thickness of substantially 0.5mm. The method 200 then proceeds to step 204.

At step 204, on the first half disc a stamper is recorded (e.g., pressed) with DVD information in a reverse direction of a typical DVD application (e.g., reverse direction as
15 DVD5) because the DVD information will be read through the second half disc. The method 200 then proceeds to step 206.

At step 206, the second half disc is recorded (e.g., pressed) as a standard high density (e.g., 0.1mm) recording (eg., Blu-ray). The method 200 then proceeds to step 208.

At step 208, the first half disc is coated with an appropriate layer-stack material for
20 DVD-R/W such as a silver or aluminum full reflective layer applied for example in a sputtering machine. The method 200 then proceeds to step 210.

At step 210, the second half disc is coated with a minimum reflective (max transmissive) coating for 405nm wavelength readability. The method 200 then proceeds to step 212.

At step 212 and prior to bonding the first half disc and the second half disc, the second
25 half disc (0.5mm substrate) is positioned (flipped) such that the data surface is on the outside of the combined disc. That is, the first half disc and the second half disc are positioned relative to each other such that the data surface of the second half disc remains on the outside (reading side) of the discs when combined and the data surface of the first half disc remains
30 between the discs when combined. The method 200 then proceeds to step 214.

At step 214, the two half discs are joined at the center using a means of DVD UV bonding known in the art (e.g., a transparent assembling adhesive layer). The method 200 then proceeds to step 216.

At step 216, the Blu-ray cover layer is coated with UV-cured lacquer to build-up the 0.1mm cover-layer required for readout of a 405nm, using for example a NA=0.85, readout device. The method 200 is then exited.

FIG. 3 depicts a high level block diagram of a high density, hybrid optical BD/CD disc 300 in accordance with an alternate embodiment of the present invention. As depicted in FIG.3, the BD/CVD disc 300 of FIG. 1 comprises a BD layer 310 and a CD layer 320. The BD/CD disc 300 is formed in such a way that the CD layer 320 on which data is recorded on the basis of the CD standard is bonded to the BD layer 310 on which data is recorded on the basis of the Blu-ray Disc standard through an adhesive layer. The high density, hybrid optical BD/CD disc 300 comprises a disc that would play in either a CD(e.g., -R/W) player (e.g., 780nm; NA=0.6) and/or a Blu-ray player (e.g., 405nm; NA=0.85.). FIG. 3 further depicts a BD laser 315 and a CD laser 325 for reading the BD data and the CD data, respectively.

More specifically, the BD/CD disc 300 of FIG. 3 uses CD/DVD half-disc bonding technology (e.g., transparent assembling adhesive layer) to make one dual-format full-thickness disc with both formats read from, in the embodiment of FIG. 3, the same side. An A-Side of a first half-disc comprises a stamper that is recorded as a regular CD(e.g., -R/W) and is made up on a half-thickness 0.6mm disc. A B-side of the original molded replica is made using a non-standard 0.5mm mold cavity. The B-side stamper is high density (e.g. Blu-ray). The B-side disc is sputtered with a high transmissive/low reflectivity coating suitable for 405nm laser (e.g. silver or silicon hydride). The B-side disc is turned over to have the sputtered data surface on the outside of the disc during bonding. The bonded disc with the B-side data surface on top is spin-coated utilizing UV-cure lacquers to build up a 0.1mm cover layer. The A-side half-disc having the CD data is also turned over so that the CD data surface is on the outside of the disc and is the bottom surface of the disc during bonding. The two half-discs having the A-side and B-side are then bonded using a DVD bonder. The bonded surfaces are the clear (non-data) surfaces of the A- and B-side substrates.

The bonded disc is printed with a label over the entire surface of the A-side disc. The CD(e.g., -R/W) layer (e.g., 780nm; NA=0.45) is read through the B-side of the disc with the infra-red laser reading through the 0.1mm spin-coated cover-layer and through the high-density data surface to reach the CD data layer molded on the A-side disc. That is, the BD layer is transparent for the infra-red laser light implemented for the CD portion. As described above, the CD portion of the disc is made up on a half-thickness 0.6mm disc and the B-side (e.g., Blu-ray portion of the disc) is made using a non-standard 0.5mm mold cavity. As such,

in the embodiment of the present invention depicted in FIG. 3, the BD layer and the CD layer are separated by a transparent spacer layer of approximately 1.1mm.

The finally bonded high density BD/CD disc 300 is configured such that the reflecting layer of the CD disc portion is located opposite to the location of the bond (e.g., adhesive layer) as depicted in FIG. 3.

FIG. 4 depicts a flow diagram of a method for manufacturing a BD/CD disc, such as the BD/CD 300 of FIG. 3, in accordance with one embodiment of the present invention. The method 400 of FIG. 4 is entered at step 402 by molding two CD (DVD) half discs using CD/DVD half disc molding technology known in the art, the CDs comprising a first disc having a thickness of substantially 0.6mm and a second disc having a thickness of substantially 0.5mm. The method 400 then proceeds to step 404.

At step 404, on the first half disc a stamper is recorded (e.g., pressed) as a regular CD(e.g., -R/W). The method 400 then proceeds to step 406.

At step 406, the second half disc is recorded (e.g., pressed) as a standard 0.1mm recording (eg., Blu-ray). The method 200 then proceeds to step 408.

At step 408, the CD(e.g., -R) manufacturing process is completed on the first half disc. The method 200 then proceeds to step 410.

At step 410, the second half disc is coated with a minimum reflective (max transmissive) coating for 405nm wavelength readability. The method 400 then proceeds to step 412.

At step 412 and prior to bonding the first half disc and the second half disc, the first half disc (0.6mm substrate) and the second half disc (0.5mm substrate) are positioned (flipped) relative to each other such that the data surfaces of the respective discs are on the outside of the discs as opposed. The method 400 then proceeds to step 414.

At step 414, the two half discs are joined at the center using a means of DVD UV bonding known in the art. The method 400 then proceeds to step 416.

At step 416, the Blu-ray 0.1mm cover layer is coated with UV-cured lacquer to build-up the 0.1mm cover-layer required for readout of a 405nm using for example a NA=0.85 readout device. The method 400 is then exited.

Having described various embodiments of high-density, hybrid optical discs and methods of manufacture of such discs (which are intended to be illustrative and not limiting), it is noted that modifications and variations can be made by persons skilled in the art in light of the above teachings. It is therefore to be understood that changes may be made in the

particular embodiments of the invention disclosed which are within the scope and spirit of the invention as outlined by the appended claims. That is, while the forgoing is directed to various embodiments of the present invention, other and further embodiments of the invention may be devised without departing from the basic scope thereof. As such, the appropriate
5 scope of the invention is to be determined according to the claims, which follow.

CLAIMS

1. Optical disc, comprising:
first and second disc portions adhesively bonded to each other, each of the disc
5 portions containing at least one transparent substrate and a data layer, the data layer of the
second disc portion being coated with a high transmissive/low reflective layer and being
situated opposite a transparent assembling adhesive layer joining said first and second disc
portions, wherein at least one of said first and second disc portions comprises a high density
format.
10
2. Optical disc according to claim 1, wherein the data layer of the first disc portion is
coated with a reflecting layer and is located adjacent to said transparent assembling adhesive
layer.
- 15 3. Optical disc according to claim 2, wherein the data layer of the first disc portion is
produced according to a DVD standard and the data layer of the second disc portion is
produced according to a Blu-ray disc (BD) standard, and in that the first and second disc
portions each have a thickness of approximately 0.6 mm.
- 20 4. Optical disc according to claim 3, wherein DVD data and BD data are read from a
common side of said optical disc.
5. Optical disc according to claim 3, wherein the data layer of the first disc portion and
the data layer of the second disc portion are separated by a transparent layer of approximately
25 0.5mm.
6. Optical disc according to claim 1, wherein the data layer of the first disc portion is
coated with a reflecting layer and is located opposite to said transparent assembling adhesive
layer.
30
7. Optical disc according to claim 6, wherein the data layer of the first disc portion is
produced according to a CD standard and the data layer of the second disc portion is produced

-10-

according to a Blu-ray disc (BD) standard, and in that the first and second disc portions each have a thickness of approximately 0.6 mm.

8. Optical disc according to claim 7, wherein CD data and BD data are read from a
5 common side of said optical disc.

9. Optical disc according to claim 7, wherein the data portion of the first elementary disc and the data portion of the second elementary disc are separated by a transparent layer of approximately 1.1mm.

10. Optical disc according to claim 1, wherein the data layers of the first and second disc portions are produced according to two mutually different standards.

11. Optical disc according to claim 1, wherein the high transmissive/low reflective layer
15 has a thickness of approximately 0.1mm.

12. Optical disc according to claim 1, wherein the high transmissive/low reflective layer is spin-coated.

13. Optical disc according to claim 1, wherein the high transmissive/low reflective layer is spin-coated utilizing UV-cure lacquers.

14. Method for manufacturing an optical disc, comprising the steps of:

producing a first disc portion by pressing at least a portion of a first transparent
25 substrate to fashion a first data layer according to a first standard, the data layer being coated with a reflecting layer;

producing a second disc portion by pressing at least a portion of a second transparent substrate to fashion a second data layer according to a second standard, the second data layer being coated with a high transmissive/low reflective layer and then protected by a protective
30 layer; and

adhesively bonding the two disc portions to each other such that the second data layer of the second disc portion is opposite the adhesive layer;

wherein at least one of said first and second disc portions comprises a high density format.

15. Method according to claim 14, wherein the first and the second disc portions are
5 bonded such that the reflecting layer of the first disc portion is adjacent to said adhesive layer.

16. Method according to claim 15, wherein the data layer of the first disc portion is
produced according to a DVD standard and the data layer of the second disc portion is
produced according to a Blu-ray disc (BD) standard, and in that the first and second disc
10 portions each have a thickness of approximately 0.6 mm.

17. Method according to claim 16, wherein DVD information is recorded in a reverse
direction of a typical DVD application during said producing.

15 18. Method according to claim 14, wherein the first and the second disc portions are
bonded such that the reflecting layer of the first disc portion is opposite said adhesive layer.

19. Method according to claim 18, wherein the data layer of the first disc portion is
produced according to a CD standard and the data layer of the second disc portion is produced
20 according to a Blu-ray disc (BD) standard, and in that the first and second disc portions each
have a thickness of approximately 0.6 mm.

20. Method according to claim 14, wherein the high transmissive/low reflective layer of
the second disc portion comprises a minimum reflective, maximum transmissive coating for
25 405nm wavelength readability.

21. A high-density, hybrid optical disc having dual formats, comprising:
a first half-disc having a high density format; and
a second half-disc having a relatively, lower density format;
30 wherein the first half-disc and the second half-disc are bonded together to make a
dual-format full-thickness optical disc such that both formats can be read from a common side
of the full-thickness optical disc.

-12-

22. A method for manufacture of a high-density, hybrid optical disc having dual formats, comprising:

recording a high density format on a first side of a first half disc;

recording a relatively, lower density format on a first side of a second half disc; and

5 bonding the first half disc to the second half disc to provide a dual-format full-thickness hybrid optical disc such that both formats can be read from a common side of the full-thickness optical disc.

23. The method of manufacture of claim 20, wherein said high density format comprises a
10 blu-ray disc (BD) high density format.

1/3




FIG. 1






FIG. 3

2/3

200**FIG. 2**

3/3

400**FIG. 4**

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2005/039321

A. CLASSIFICATION OF SUBJECT MATTER G11B20/12 G11B7/007 G11B7/24		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) G11B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the International search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data, PAJ		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 23, 10 February 2001 (2001-02-10) - & JP 2001 176129 A (VICTOR CO OF JAPAN LTD), 29 June 2001 (2001-06-29) the whole document	1-23
A	US 6 434 107 B1 (ARTIGALAS MAX ET AL) 13 August 2002 (2002-08-13) the whole document	1-23
A	WO 98/31011 A (WEA MANUFACTURING, INC; MARQUARDT, RICHARD, JR; COOKSON, CHRISTOPHER;) 16 July 1998 (1998-07-16) abstract page 1, line 1 - page 6, line 27 figures 1-3	1-23
----- -/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the International filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the international search 15 February 2006		Date of mailing of the international search report 12/06/2006
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Sucher, R

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2005/039321

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 12, 5 December 2003 (2003-12-05) & JP 2003 308631 A (RICOH CO LTD), 31 October 2003 (2003-10-31) abstract	1-23
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 09, 30 July 1999 (1999-07-30) & JP 11 120617 A (SONY CORP), 30 April 1999 (1999-04-30) abstract	1-23
A	US 5 732 065 A (BRAAT ET AL) 24 March 1998 (1998-03-24) the whole document	1-23
A	EP 0 745 985 A (VICTOR COMPANY OF JAPAN, LIMITED) 4 December 1996 (1996-12-04) abstract column 6, line 29 - column 11, line 59 figures 4-6	1-23
A	EP 0 520 619 A (PIONEER ELECTRONIC CORPORATION) 30 December 1992 (1992-12-30) abstract column 2, line 43 - column 4, line 22 figures 3,4	1,14,21, 22

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/US2005/039321

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 2001176129	A	29-06-2001	NONE
US 6434107	B1	13-08-2002	AT 255266 T 15-12-2003 BR 9706549 A 20-07-1999 CN 1196817 A 21-10-1998 CN 1558412 A 29-12-2004 DE 69726387 D1 08-01-2004 DE 69726387 T2 16-09-2004 EP 0847580 A1 17-06-1998 ES 2212111 T3 16-07-2004 FR 2750528 A1 02-01-1998 WO 9800842 A1 08-01-1998 HK 1015514 A1 25-02-2005 ID 17785 A 29-01-1998 JP 11511889 T 12-10-1999
WO 9831011	A	16-07-1998	AU 5819098 A 03-08-1998 EP 0928482 A2 14-07-1999
JP 2003308631	A	31-10-2003	NONE
JP 11120617	A	30-04-1999	NONE
US 5732065	A	24-03-1998	CA 2204496 A1 13-03-1997 CN 1165575 A 19-11-1997 CZ 9701298 A3 15-10-1997 DE 69627811 D1 05-06-2003 DE 69627811 T2 11-03-2004 ES 2195004 T3 01-12-2003 HU 9801353 A2 28-08-1998 WO 9709716 A1 13-03-1997 JP 10508974 T 02-09-1998 PL 320023 A1 01-09-1997 PT 796492 T 30-09-2003 RU 2181509 C2 20-04-2002
EP 0745985	A	04-12-1996	DE 69622471 D1 29-08-2002 DE 69622471 T2 08-05-2003 JP 3008819 B2 14-02-2000 JP 8329523 A 13-12-1996 US 5696754 A 09-12-1997
EP 0520619	A	30-12-1992	JP 5006571 A 14-01-1993